

## **Section 1: Identification**

**Product identifier:** 

Product Name(s)

TSX-8500 TSX-8510

Relevant identified uses of the substance or mixture and uses advised against

Recommended use Insulation Board

Details of the supplier of the safety data sheet Manufacturer

Rmax Operating, LLC 13524 Welch Road Dallas, TX 75244 United States

www.rmax.com

Rmax@rmax.com

Telephone (General) 972-387-4500

Emergency telephone number only:

Call CHEMTREC

Day or Night within USA and Canada:

1-800-424-9300

## **Section 2: Hazard Identification**

**United States (US)** 

Classification of the substance or mixture OSHA HCS 2012 Not classified

**Label elements**OSHA HCS 2012

Hazard statements No label element(s) required

Other hazards

OSHA HCS 2012 This product is not considered hazardous under the U.S. OSHA 29 CFR 1910.1200

Hazard Communication Standard.

## Section 3 - Composition/Information on Ingredients

**Substances** Material does not meet the criteria of a substance.

#### Mixtures

Composition (varies with product thickness)					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/ Directive	
Polyisocyanurate Foam	CAS:9063-78-9	99%	No data available	OSHA HCS 2012: Not Classified	
Pentane	CAS:109-66-0	0% to 5%	Inhalation-Rat LC50 364 g/m <sup>3</sup> 4 Hour(s); Ingestion/Oral-Rat LD50 >2000 mg/kg	OSHA HCS 2012: Flam. Liq. 1; STOT SE 3: Narc.; Asp. Tox. 1	
Aluminum Foil Laminations	None	1%	No data available	OSHA HCS 2012: Not Classified	
∟Aluminum [< 1%]	CAS:7429-90-5	<0.01%	NDA No data available	OSHA HCS 2012: Exposure limits	
Glass, oxide, chemicals	CAS:65997-17-3	0.01%	No data available	OSHA HCS 2012: Exposure limits	

Revision Date: 07/20/2015 Page 1 of 5



### **Section 4: First-Aid Measures**

Description of first aid measures

Inhalation First aid is not expected to be necessary if materials used under ordinary conditions and as

recommended. If signs/symptoms develop, get medical attention.

Skin First aid is not expected to be necessary if materials used under ordinary conditions and as

recommended. If signs/symptoms develop, get medical attention.

Eye In case of contact with substance, immediately flush eyes with running water for at least 20

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If signs/

symptoms develop, get medical attention.

Ingestion First aid is not expected to be necessary if materials used under ordinary conditions and as

recommended.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Immediate medical attention after exposure to this material not expected to be necessary. No

special treatment indicated related to exposure to this material.

## **Section 5: Fire-Fighting Measures**

**Extinguishing media** 

Suitable Extinguishing Media LARGE FIRE: Water spray, fog or regular foam.

SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable Extinguishing Media None known

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards Polyisocyanurate foam is combustible.

Hazardous Combustion Products Carbon dioxide and carbon monoxide

Advice for fire fighters Fire fighters should wear complete protective clothing including self-contained

breathing apparatus. Structural fire fighters' protective clothing will only provide

limited protection.

### Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions No special precautions expected to be necessary if materials used under ordinary

conditions and as recommended.

Emergency Procedures No emergency procedures are expected to be necessary if materials used under

ordinary conditions as recommended.

**Environmental precautions** No special environmental precautions necessary.

Methods and material for containment and cleaning up

Containment/Clean-up Measures Pick up pieces and vacuum clean dusts. If sweeping is necessary, use a dust

suppressant.

Revision Date: 07/20/2015 Page 2 of 5



## **Section 7 - Handling and Storage**

Precautions for safe handling

Handling

Use only with adequate ventilation. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Avoid breathing dusts generated during use of this material. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

### Conditions for safe storage, including any incompatibilities

Storage Keep away from heat, sparks, and flame. Keep away from incompatible materials.

Store in a cool, dry place.

# **Section 8 - Exposure Controls/Personal Protection**

**Control parameters** 

	Result	ACGIH	NIOSH	OSHA
	TWAs	1000 ppm TWA (listed under Pentane, all	120 ppm TWA; 350 mg/m3 TWA	1000 ppm TWA; 2950 mg/m3
Pentane		isomers)		TWA
(109-66-0)	Ceilings		610 ppm Ceiling (15 min); 1800 mg/m3	Not established
			Ceiling (15 min)	
Aluminum	TWAs	1 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA (total dust); 5 mg/m3	15 mg/m3 TWA (total dust); 5
(7429-90-5)			TWA (respirable dust)	mg/m3 TWA respirable fraction)
Glass, oxide,	TWAs	1 fiber/cm3 TWA (respirable fibers: length	3 fiber/cm3 TWA (fibers <= 3.5 μm in	Not established
chemicals		>5 μm, aspect ratio >=3:1, as determined by	diameter and >= 10 μm in length); 5	
as Glass		the membrane filter method at 400-450X	mg/m3 TWA (total), as Glass wool fiber	
wool fiber		magnification [4-mm objective], using phase-		
		contrast illumination, listed under Synthetic		
		vitreous fibers), as Glass wool fiber		

#### **Exposure controls**

Engineering Measures/Controls Adequate ventilation systems as needed to control concentrations of airborne

contaminants below applicable threshold limit values.

**Personal Protective Equipment** 

Respiratory In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/Face Wear safety glasses or goggles

Skin/Body No skin protection is ordinarily required under normal conditions of use. Protective

puncture-resistant gloves and/or sleeves for handling rough-cut edges.

**Environmental Exposure Controls** Follow best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene
NIOSH = National Institute of Occupational Safety and Health
OSHA = Occupational Safety and Health Administration
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

# **Section 9 - Physical and Chemical Properties**

**Information on Physical and Chemical Properties** 

Material Description						
Physical Form	Solid	Appearance/ Description	Rigid foam board with foil facers - various thicknesses.			
Color White/cream foam		Odor	Odorless			
General Properties						
Boiling Point	Not relevant	Melting Point	No data available			
Decomposition Temperature	No data available	рН	Not relevant			
Specific Gravity/Relative Density	= 0.03 Water=1	Water Solubility	Not relevant			

Revision Date: 07/20/2015 Page 3 of 5



Volatility					
Vapor Pressure	No data available	Vapor Density	No data available		
Evaporation Rate	No data available				
Flammability					
Flash Point Not relevant		UEL	Not relevant		
LEL	Not relevant	Auto ignition	No data available		
Flammability (solid, gas)	No data available				

## **Section 10: Stability and Reactivity**

**Reactivity** No dangerous reaction known under conditions of normal use.

**Chemical stability** Stable under normal temperatures and pressures.

Possibility of hazardous reactions Hazardous polymerization will not occur.

**Conditions to avoid** Sources of flame and ignition.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Under normal conditions, hazardous decomposition will not occur. Thermal

decomposition may emit fumes or gases, such as carbon monoxide, carbon

dioxide.

# **Section 11 - Toxicological Information**

Information on toxicological effects

into mation on toxicological enects				
Components				
Pentane (0% TO 5%)	109-66-0	Acute Toxicity: Ingestion/ Oral-Rat LD50 >2000 mg/kg; Inhalation-Rat LC50 364 g/m <sup>3</sup> 4 Hour(s)		

#### **Potential Health Effects**

Inhalation

Acute (Immediate) Exposure to dust may cause irritation.

Skin

Acute (Immediate) Causes mild skin irritation.

Eye

Acute (Immediate) Exposure to dust may cause mechanical irritation.

Ingestion

Acute (Immediate) Excessive concentrations of nuisance dust in the workplace may cause mechanical

irritation to mucous membranes.

**Carcinogenic Effects** 

Glass, oxide, chemicals as Glass wool fiber National Toxicology Program (NTP): reasonably anticipated to be

Human Carcinogen

**Key to abbreviations** TD = Toxic Dose

## **Section 12 - Ecological Information**

**Toxicity and ecological data** No information available.

Revision Date: 07/20/2015 Page 4 of 5



## **Section 13 - Disposal Considerations**

Waste treatment methods

**Product waste** Dispose of content and/or container in accordance with local, regional, national,

and/or international regulations.

**Packaging waste** Dispose of content and/or container in accordance with local, regional, national,

and/or international regulations.

## **Section 14 - Transport Information**

DOT, TDG, IMO/IMDG, IATA/ICAO Not regulated.

**Special precautions for user** None specified.

**Transport in bulk according to Annex II of MARPO73/78 and the IBC Code**No data available

## **Section 15 - Regulatory Information**

 $Safety, health \ and \ environmental \ regulations/legislation \ specific \ for \ the \ substance \ or \ mixture$ 

**SARA Hazard Classifications** None

	State Right To Know				
Component	CAS	MA	NJ	PA	TSCA
Aluminum	7429-90-5	Yes	Yes	Yes	Yes
Pentane	109-66-0	Yes	Yes	Yes	Yes
Glass oxide, chemicals	65997-17-3	No	No	No	Yes
Polyisocyanurate Foam	9063-78-9	No	No	No	Yes

OSHA - Process Safety Management, Highly Hazardous Chemicals
OSHA - Specifically Regulated Chemicals
Clean Air Act (CAA) - 1990 Hazardous Air Pollutants

Not Listed
Not Listed

**CERCLA/SARA - Section 313 - Emission Reporting** 

Aluminum 7429-90-5 1.0 % de minimis concentration (dust or fume only)

**California - Proposition 65** Not Listed

### **Section 16 - Other Information**

**Preparation Date:** 05/29/2015 **Last Revision Date:** 07/20/2015

### **Disclaimer/Statement of Liability**

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, express or implied, regarding its accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product.

Revision Date: 07/20/2015 Page 5 of 5